

High Frequency Press - Dual Table

Made in Taiwan

SPECIFICATIONS:

Input Power: 3 Ø 415V

High Frequency Power: 25 KW

Transmitting Tube: 8T25RA CANON Made in Japan

H.F. Adjustor Hand wheel adjustor

High Tension Transformer: AC8000V, DC10000V. 40KVA Made in Taiwan

Rectifier Patented, High Tension resistance, Full wave Made in Taiwan

Variable Capacitor Patented, 4 piece one Set,

Press Work Range Max: 1220 X 2440 X 15~50mm

Pressure Apply □V: 5HP Hydraulic system Made in

Taiwan

Pressing Way Upper and Side pressure

Cylinders: UP× 4 PCS / Side x 4 PCS / Rear 8PCS Made in Taiwan

Inlet feeding Table Motor drive chained Pusher Made in Taiwan

Anti-Glue-Stick Upper plate with Anti-Glue-Stick to prevent glue from stick on Made in Japan

Protection: Tube Protector Patented tube protector is to protect the expensive tube from

over-heat burnt Made

in Taiwan

Spark Suppressor Patented spark suppressor is to protect machine plate and work piece from short voltage burnt

Made in Taiwan

Grounding Whole plate grounding

Anti Clamp Protection Equipped 2 fences at entrance of inlet and outlet

Control system Standard control system

Made in Taiwan

Made in Taiwan

Dimension L:5600mm W:2200mm H: 2100mm

Weight NW:5600KGS. GW:5950KGS.









Sales@fewcut.com