

WIDE BELT SANDER

MADE IN TAIWAN

SPECIFICATIONS:

MAX. WORKING WIDTH:	1300 MM
MAX. WORKING THICKNESS:	3-130 MM
N SPIRAL CUTTING HEAD DIA:	φ160 MOTOR: 25HP
R. RUBBER WHEEL DIAMETER:	φ220 MOTOR:25HP
P RUBBER WHEEL DIAMETER:	φ130 MOTOR:20HP
PROLLER WHEEL DIAMETER:	110
FEEDING POWER:	5HP (VARIABLE SPEED FEED FATE.)
TABLE HOIST POWER:	1/2HP
SANDING BELT SIZE:	52" X 75"
SPIRAL CUTTING BLADE SIZE:	15*15*2.5 MM.

THICKNESS DIGITAL CONTROLLER / PRESSING USE PRESSING ROLLER

PRESSURE SWITCH: WHEN COMPRESSED AIR IS INSUFFICIENT, MACHINE WILL AUTOMATICALLY STOP

ANTI-KICKBACK FINGERS: ANTI-KICKBACK FINGERS ARE BUILT IN FRONT OF SPIRAL CUTTERHEAD, ELIMINATION THE DANGER OF PANEL

KICKBACK AND ENSURING THE IPERATOR

PIANO-KEY TYPE INFEED PRESSURE JAWS: THE SPECIALLY DESIGNED PIANO-KEY TYPE INFEED PRESSURE JAWS ARE MOUNTED AT

THE INFEED END. IT ASSURES SMOOTH FEEDING PERFORMANCE REGARDLESS OF WOOD THICKNESS VARIATION

ANTI-EXPLOSION SWITCH: WHEN SANDING BELT IS BROKEN POWER OFF AUTO AND CONVEYOR WILL DOWN AUTO TO PROTECT CONVEYOR AND RUBBER ROLLER.



18, Shree Gopal Nagar,
Near 21 No. Bus Stand Panchyawala,
Sirsi Road, Jaipur - 302034 INDIA



+91-8890337607



falgunienterprises0107@gmail.com
contact@fewcut.com
Sales@fewcut.com